



## TeleControl Serie 24 , 12 Botones , 1 Velocidad, Alcance 100Mts

### Características Esenciales

- 1 Años de Garantía, Partes y Servicios Disponibles en América

## Especificaciones Técnicas

<b>Control Speed</b>	1 Speed	<b>Código de Seguridad</b>	32 bits (4.3 billion)
<b>Channels</b>	12	<b>Potencia del Transmisor</b>	≤10dBm
<b>Transmitter Emergency Stop</b>	Yes	<b>Rango de Frecuencia</b>	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
<b>Código FCC</b>	OFNF21	<b>Rango de temperatura de Trabajo</b>	-40 ~ 185 °F / -40 ~ 85°C
<b>Fuente de Alimentación del Transmisor</b>	2 AA batteries	<b>Normas</b>	FCC and OSHA standard 1910.179
<b>Distancia de Control</b>	300 ft up to 600 ft with optional antenna	<b>Garantía</b>	1 Year



**MODEL: F24-12S**  
**ITEM CODE: 24-012-001**  
**Dimensions: 186 x 61 x 51 mm**  
**Weight: 280g (without batteries)**



**Product Features:**

- 7-12 buttons (D means double steps), STOP, START, spare buttons
- Up to 20 control contacts..
- With battery voltage warning device, the power supply is cut off during low power.
- Safety switch key to prevent from unauthorized user.
- Program the button function by computer interface.
- Up/Down, East/West, North/South can be programmed to interlock or non-interlock.
- Power key can be programmed to start, toggle switch, normal or other functions.
- The spare buttons can be programmed to normal, interlock, toggle or start, etc.

#### Transmitter Parameters: F24-12S

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C + 85° C
Control distance	Approx 100m (200 meters is customized)

#### Standard Configuration:

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- One receiver antenna
- Operation and maintenance manual.

#### Safety features:

Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.



F24 series remote control system have 80 channels in its frequency range. Even in situations where many sets of remote control are used in the same time, working channel can be easily chosen without interfering with other signals and hundred-percent safe reliable. With advanced design and high quality components, the system is durable and easy to operate. It can easily adapt to complicated and harsh industrial environments such as extra-high/low temperature, dusty, strong vibration, greasy, heavy humidity, etc.

Transmitter and receiver have many functions used in conjunction. The emergency stop button is located in the upper left of the transmitter which meets the safety and ergonomics. When stop button is pressed, the system stops working immediately and unconditionally. Transmitter is equipped with a shell of more consistent with ergonomics. The new shell material is more durable, lighter and thinner.

**MODEL: F24-RXC**  
**ITEM CODE: 924-100-102-112**  
**Dimensions: 210 x 162 x 107 mm**  
**Weight: 1220g**



#### Transmitter Parameters: F24-RXC

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	18~65V AC/DC, 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 100m (200 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C + 85° C



## Peso & Dimensiones

**Peso Total**

6 lbs / 3 Kg

Referential Images / Imágenes Referenciales

Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso