




Tecle Cadena - Neumatico Anti explosion de 1,5 Tons ATEX - Nickel kit

Características Esenciales

- 1.5 Ton Pneumatic Chain Hoist - Heavy Duty - Explosion Proof - Nickel Kit
- Nickel Coated: Chain hook, bottom block, Sprocket, Load sleeve, Safety Catch
- Includes: Overload Protection - Slip Clutch / Failsafe Automatic Internal Break / Pendant Control with emergency stop / Chain containers
- Meets and exceeds ASME B30.16 / HST-5 standards / Load Test at 130% SWL / ATEX Directive
- 3 Años de Garantía, Partes y Servicios Disponibles en América

Especificaciones Técnicas

Capacidad de Carga	1.5 Ton	Caidas de Cadena	1
Altura de Izaje Estandar (Customizable)	20 ft / 6 m	Temperatura	-20°C to 70°C
Numero de Velocidades	1 Speed	Nivel de Ruido	83 dBA @ 1m
Protección Antiexplosión	- EX 2 GD IIA T4 EX 2 GD IIB T4 EX 2 GD IIC T4 ZONES 1, 2 AND 21, 22 - Nickel Coated: Chain hook, bottom block, Sprocket, Load sleeve, Safety Catch	Normas	ASME B30.11 /B30.16 /HST-5 DIN EN818-7 SANS 1638 compliant ATEX EX Classification according to EC Directive on Hazardous Locations 94/9/EEC
Clase de Servicio	100% Duty Cycle	Fabricado en	South Africa
Freno Motor	>125% WLL Automatic self-adjusting multidisc Brake	Garantía	3 Year
Control	Pendant Control w/emergency stop	Pendant Control Yes No	Included
Tipo Transmisión / Reductor	Epicycle Gearbox (Grease Filled and Sealed)	IEC Pendant Control Protection	IP66
Tipo de Cadena	G80 RUD Germany 5:1 Safety Factor	Pendant Control Emergency Stop	Yes
Dimensiones de la Cadena	9 x 27 mm		



Dimensions in mm / Dimensiones en mm

Detalles del Empaque

H Altura Muerta	361 mm
W Ancho	384 mm
D Depth	143 mm
J Boca Gancho	25 mm

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso